

**Safety data sheet**  
according to 1907/2006/EC, Article 31

**TETENAL**

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name: **Kameralack Spray- Camera varnish black, deep matt**

Article number: 105202

Index number:

None of the ingredients is listed.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

### Application of the substance / the mixture

Auxiliary product for photographic processing

Lacquer to repair cameras, lens, optical apparatuses

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

TETENAL 1847 GmbH

Schützenwall 31-35

D-22844 Norderstedt /Germany

Tel.: +49 (0) 40 521 45-0; Fax: +49 (0)40-52145-296

www.tetenal.com; E-mail: info@tetenal.com

TETENAL 1847 GmbH

Schützenwall 31-35

D-22844 Norderstedt /Germany

Tel.: +49 (0) 40 521 45-0; Fax: +49 (0)40-52145-296

www.tetenal.com; E-mail: info@tetenal.com

Further information obtainable from: Department product safety. E-Mail: sida@tetenal.com

### 1.4 Emergency telephone number:

Poison Information Centre Germany: +49 (0) 30 - 30686 700 (English and German 24 hours)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

#### Hazard pictograms



GHS02

GHS07

GHS09

Signal word Danger

#### Hazard-determining components of labelling:

Acetic ether

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

#### Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

(Contd. on page 2)

EN

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

### Trade name: Kameralack Spray- Camera varnish black, deep matt

(Contd. of page 1)

H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

#### Precautionary statements

P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P251 Do not pierce or burn, even after use.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

· **PBT:** Not applicable.  
 · **vPvB:** Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below and with nonhazardous additions.

#### Dangerous components:

CAS: 106-97-8	butane, pure	10-<25%
EINECS: 203-448-7	⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Index number: 601-004-00-0		
CAS: 141-78-6	Acetic ether	10-<25%
EINECS: 205-500-4	⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	
Index number: 607-022-00-5		
Reg.nr.: 01-2119475103-46		
CAS: 74-98-6	propane	10-<25%
EINECS: 200-827-9	⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Index number: 601-003-00-5		
CAS: 64742-49-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclically	10-<25%
EINECS: 265-151-9	⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	
Index number: 649-328-00-1		
CAS: 75-28-5	isobutane	5-10%
EINECS: 200-857-2	⚠ Flam. Gas 1, H220; Press. Gas (Comp.), H280	
Index number: 601-004-00-0		
CAS: 68920-06-9	Hydrocarbons, C7-9	1-5%
EC number: 920-750-0	⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 92128-66-0	Hydrocarbons, C6-7	1-5%
EC number: 926-605-8	⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	
Reg.nr.: 01-2119475514-35		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	1-5%
EINECS: 203-603-9	⚠ Flam. Liq. 3, H226	
Index number: 607-195-00-7		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	1-5%
EINECS: 265-199-0	⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336	
Index number: 649-356-00-4		
Reg.nr.: 01-2119455851-35		
CAS: 110-82-7	cyclohexane	1-5%
EINECS: 203-806-2	⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Acute 1, H400; ⚠ Aquatic Chronic 1, H410; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	
Index number: 601-017-00-1		

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 2)

CAS: 110-54-3 n-hexane <1%  
 EINECS: 203-777-6 ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; Asp.  
 Index number: 601-037-00-0 Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315;  
 STOT SE 3, H336

. **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### . 4.1 Description of first aid measures

- . **General information:** Immediately remove any clothing/shoes soiled by the product.
- . **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- . **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- . **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- . **After swallowing:** Do not induce vomiting; call for medical help immediately.

#### . 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### . 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

#### . 5.1 Extinguishing media

- . **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- . **For safety reasons unsuitable extinguishing agents:** Water with full jet

#### . 5.2 Special hazards arising from the substance or mixture

Nitrogen oxides (NO<sub>x</sub>)  
 Carbon monoxide (CO)  
 Sulphur dioxide (SO<sub>2</sub>)  
 Under certain fire conditions, traces of other toxic gases cannot be excluded.

#### . 5.3 Advice for firefighters

- . **Protective equipment:** Do not inhale explosion gases or combustion gases.

### SECTION 6: Accidental release measures

#### . 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.  
 Ensure adequate ventilation

#### . 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.  
 Inform respective authorities in case of seepage into water course or sewage system.  
 Do not allow to enter sewers/ surface or ground water.

#### . 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.  
 Do not flush with water or aqueous cleansing agents

#### . 6.4 Reference to other sections

See Section 7 for information on safe handling.  
 See Section 8 for information on personal protection equipment.  
 See Section 13 for disposal information.

### SECTION 7: Handling and storage

#### . 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.  
 Open and handle receptacle with care.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 3)

**. Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

**. 7.2 Conditions for safe storage, including any incompatibilities**

**. Storage:**

**. Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurised containers.

**. Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from flammable substances.

Store away from oxidising agents.

**. Further information about storage conditions:**

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store under lock and key and out of the reach of children.

Recommended storage temperature: 5-30°C

**. 7.3 Specific end use(s) No further relevant information available.**

## SECTION 8: Exposure controls/personal protection

**. Additional information about design of technical facilities:** No further data; see item 7.

**. 8.1 Control parameters**

**. Ingredients with limit values that require monitoring at the workplace:**

**106-97-8 butane, pure**

WEL (Great Britain) Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
 Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
 Carc (if more than 0.1% of buta-1.3-diene)

REL (USA) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

TLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm  
 (EX)

**141-78-6 Acetic ether**

WEL (Great Britain) Short-term value: 400 ppm  
 Long-term value: 200 ppm

IOELV (EU) Short-term value: 1468 mg/m<sup>3</sup>, 400 ppm  
 Long-term value: 734 mg/m<sup>3</sup>, 200 ppm

PEL (USA) Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

REL (USA) Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm

TLV (USA) Long-term value: 1440 mg/m<sup>3</sup>, 400 ppm

**74-98-6 propane**

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

REL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm

TLV (USA) refer to Appendix F in TLVs&BEIs book; D, EX

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 4)

**75-28-5 isobutane**

TLV (USA) Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm  
(EX)

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL (Great Britain) Short-term value: 548 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 274 mg/m<sup>3</sup>, 50 ppm  
Sk

IOELV (EU) Short-term value: 550 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 275 mg/m<sup>3</sup>, 50 ppm  
Skin

WEEL (USA) Long-term value: 50 ppm

**110-82-7 cyclohexane**

WEL (Great Britain) Short-term value: 1050 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 350 mg/m<sup>3</sup>, 100 ppm

IOELV (EU) Long-term value: 700 mg/m<sup>3</sup>, 200 ppm

PEL (USA) Long-term value: 1050 mg/m<sup>3</sup>, 300 ppm

REL (USA) Long-term value: 1050 mg/m<sup>3</sup>, 300 ppm

TLV (USA) Long-term value: 344 mg/m<sup>3</sup>, 100 ppm

**110-54-3 n-hexane**

WEL (Great Britain) Long-term value: 72 mg/m<sup>3</sup>, 20 ppm

IOELV (EU) Long-term value: 72 mg/m<sup>3</sup>, 20 ppm

PEL (USA) Long-term value: 1800 mg/m<sup>3</sup>, 500 ppm

REL (USA) Long-term value: 180 mg/m<sup>3</sup>, 50 ppm

TLV (USA) Long-term value: 176 mg/m<sup>3</sup>, 50 ppm  
Skin; BEI

**Ingredients with biological limit values:****110-54-3 n-hexane (<1%)**

BEI (USA) 0.4 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: 2,5-Hexanedione without hydrolysis

**Additional information:** The lists valid during the making were used as basis.

**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

**Respiratory protection:**

Filter A/P2 Filter against organic gases and vapors with boiling point > 65 ° C and liquid particles against gesundheitsschädlicher Stoffe

Ensure adequate ventilation

**Protection of hands:**

Protective gloves

Impervious gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 5)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR  
Nitrile rubber, NBR  
Neoprene gloves

**Penetration time of glove material**

Glove material	breakthrough-time	layer thickness
Butyl rubber:	≥480 min	≥0,4mm
Nitrile rubber:	≥480 min	≥0,38mm
Neoprene:	≥240 min	≥0,65mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:**



Tightly sealed goggles

**Body protection:** Protective work clothing

### SECTION 9: Physical and chemical properties

**9.1 Information on basic physical and chemical properties**

**General Information**

**Appearance:**

<b>Form:</b>	Aerosol
<b>Colour:</b>	Black
<b>Odour:</b>	Characteristic
<b>Odour threshold:</b>	Not determined.

**pH-value:** Not determined.

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	Not applicable, as aerosol.

**Flash point:** -60 °C

**Flammability (solid, gas):** Not applicable.

**Ignition temperature:** ~200 °C

**Decomposition temperature:** Not determined.

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Not determined.

**Explosion limits:**

<b>Lower:</b>	1.5 Vol %
<b>Upper:</b>	11.5 Vol %

**Vapour pressure at 20 °C:** 3,500 hPa

**Density at 20 °C:** 0.65 g/cm<sup>3</sup>

**Relative density** Not determined.

**Vapour density** Not determined.

**Evaporation rate** Not applicable.

(Contd. on page 7)

EN

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 6)

<b>. Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>. Partition coefficient: n-octanol/water:</b>	Not determined.
<b>. Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.
<b>. Solvent content:</b>	
<b>Organic solvents:</b>	84.6 %
<b>VOC (EC)</b>	609 g/l
<b>Solids content:</b>	0.0 %
<b>. 9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- . **10.1 Reactivity** No further relevant information available.
- . **10.2 Chemical stability**
- . **Thermal decomposition / conditions to be avoided:** Stable at environment temperature.
- . **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- . **10.4 Conditions to avoid** No further relevant information available.
- . **10.5 Incompatible materials:** Under certain fire conditions, traces of other toxic gases cannot be excluded.
- . **10.6 Hazardous decomposition products:**  
Irritant gases/vapours  
Carbon monoxide and carbon dioxide

### SECTION 11: Toxicological information

- . **11.1 Information on toxicological effects**
  - . **Acute toxicity** Based on available data, the classification criteria are not met.
  - . **LD/LC50 values relevant for classification:**
- 
- 141-78-6 Acetic ether**  
Oral LD50 4,935 mg/kg (rat)  
Inhalative LC50 4 mg/l (rat)
- 64742-49-0 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclically**  
Oral LD50 >2,000 mg/kg (rat)  
Dermal LD50 >2,000 mg/kg (rabbit)  
Inhalative LC50 4 mg/l (rat)
- 108-65-6 2-methoxy-1-methylethyl acetate**  
Oral LD50 8,532 mg/kg (rat)
- 110-82-7 cyclohexane**  
Oral LD50 12,705 mg/kg (rat)
- . **Primary irritant effect:**
  - . **Skin corrosion/irritation**  
Causes skin irritation.
  - . **Serious eye damage/irritation**  
Causes serious eye irritation.
  - . **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
  - . **Acute effects (acute toxicity, irritation and corrosivity)**  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant

(Contd. on page 8)

EN



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 7)

- . **CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)**
- . **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- . **Carcinogenicity** Based on available data, the classification criteria are not met.
- . **Reproductive toxicity** Based on available data, the classification criteria are not met.
- . **STOT-single exposure**  
May cause drowsiness or dizziness.
- . **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- . **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- . **12.1 Toxicity**
- . **Aquatic toxicity:**
- . **141-78-6 Acetic ether**  
EC50 48 mg/l (daphnia magna (Water flea))  
LC50 96 mg/l (fish: Oncorhynchus mykiss)
- . **64742-49-0 Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclically**  
EC50 10-96 mg/l (alg)  
10-48 mg/l (daphnia magna (Water flea))
- . **12.2 Persistence and degradability** No further relevant information available.
- . **12.3 Bioaccumulative potential** No further relevant information available.
- . **12.4 Mobility in soil** No further relevant information available.
- . **Ecotoxicological effects:**
- . **Remark:** Toxic for fish
- . **Additional ecological information:**
- . **General notes:**  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms
- . **12.5 Results of PBT and vPvB assessment**
- . **PBT:** Not applicable.
- . **vPvB:** Not applicable.
- . **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- . **13.1 Waste treatment methods**
- . **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- . **European waste catalogue**
- . 15 01 10\* packaging containing residues of or contaminated by hazardous substances
- . 15 01 04 metallic packaging
- . **Uncleaned packaging:**
- . **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- . **14.1 UN-Number**
- . **ADR, IMDG, IATA** UN1950

(Contd. on page 9)



## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 8)

. 14.2 UN proper shipping name	
. ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
. IMDG	AEROSOLS, MARINE POLLUTANT
. IATA	AEROSOLS, flammable
. 14.3 Transport hazard class(es)	
. ADR	
. Class	2 5F Gases.
. Label	2.1
-----	
. IMDG, IATA	
. Class	2.1
. Label	2.1
. 14.4 Packing group	
. ADR, IMDG, IATA	Void
. 14.5 Environmental hazards:	
. Marine pollutant:	No
	Symbol (fish and tree)
. Special marking (ADR):	Symbol (fish and tree)
. 14.6 Special precautions for user	
. Hazard identification number (Kemler code):	-
. EMS Number:	F-D,S-U
. Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
. Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
. 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	
	Not applicable.
. Transport/Additional information:	
-----	
. ADR	
. Limited quantities (LQ)	1L
. Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
. Transport category	2
. Tunnel restriction code	D
-----	
. IMDG	
. Limited quantities (LQ)	1L
. Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
. UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

EN

(Contd. on page 10)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

(Contd. of page 9)

### SECTION 15: Regulatory information

- . **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
  - . **Labelling according to Regulation (EC) No 1272/2008** GHS label elements
  - . **Directive 2012/18/EU**
  - . **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
  - . **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
  - . **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 57
  - . **National regulations:**
  - . **Regulation (EC) No 648/2004 on detergents / Labelling for contents**
- |                        |      |
|------------------------|------|
| aliphatic hydrocarbons | ≥30% |
| aromatic hydrocarbons  | <5%  |
- . **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- . **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- . **Contact:** E: sida@tetenal.com
- . **Abbreviations and acronyms:**
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Gas 1: Flammable gases – Category 1
- Aerosol 1: Aerosols – Category 1
- Press. Gas (Comp.): Gases under pressure – Compressed gas
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 27.10.2020

version no: 7

Revision: 27.10.2020

**Trade name: Kameralack Spray- Camera varnish black, deep matt**

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

(Contd. of page 10)

**\* Data compared to the previous version altered.**

EN